



# FM2819 (File number: S&CIC1083) LED

Miner's lamp control IC

## One, Overview

This IC is a special integrated circuit designed for LED miner's lamp, using the most advanced control technology and wide voltage design. Strengthens the durability of IC

It can be used to control LED lights of 3W or below, with current limiting protection function, over temperature protection function, output short circuit protection function, anti-reverse battery connection function can.

The chip changes the current of the LED lamp by changing the size of the external resistor R1; it is controlled by tapping the switch button: strong light → dark light → flashing, so follow Ring; when long press the button has SOS function.

## two, Features

- Working voltage: 2.5V~4.5V
- Working current: <1mA
- Working temperature: ≤85°C
- Maximum power consumption: 0.5uA
- Current limiting protection function
- Over-temperature protection function
- Output short circuit protection function
- Anti-reverse battery protection function
- Package: SOT23-6

## three, Applications

- Mainly used in high-power LED headlights and other lamps.

## four, Pin diagram and pin description

SOT23-6

Serial number	Pin	Pin description
1	NC	Dangling
2	GND	Power negative
3	NC	Dangling
4	LED	Signal output (LED negative output)
5	SW	Trigger switch
6	VCC	Positive power supply



FM2819 (File number: S&CIC1083) LED

Miner's lamp control IC

Fives, Electrical parameters (Ta=25°C, VCC=3.7V, LED=1W unless otherwise stated)

symbol	parameter	Test Conditions	Minimum value	Typical value	Maximum	unit	
Icc	Working current	After starting	bright	60	80	100	etc.
			1/4 bright	70	90	110	
			flicker	60	80	100	
			Extinguish	-	0	-	
			Long press SOS	60	80	100	
Vcc	Operating Voltage	start up	-	2.5	-	V	
		Shut down	-	2.0	-		
f <sub>LED</sub>	LED switching waveform frequency	Half bright	-	sixteen	-	Khz	
		flicker	-	8	-	HZ	
Ron	On-resistance	-	-	110	-	mΩ	
I <sub>max</sub>	Maximum fluency	-	-	2.4	-	A	
Thousand	Over temperature protection point	Shut down	-	190	-	°C	
		restore	-	175	-	°C	

6. Typical application circuit diagram

