



ON Semiconductor®

## 74AC08, 74ACT08 Quad 2-Input AND Gate

### Features

- $I_{CC}$  reduced by 50% on 74AC only
- Outputs source/sink 24mA

### General Description

The AC08/ACT08 contains four, 2-input AND gates.

### Ordering Information


| Order Number | Package Number | Package Description                                                          |
|--------------|----------------|------------------------------------------------------------------------------|
| 74AC08SC     | M14A           | 14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow |
| 74AC08SJ     | M14D           | 14-Lead Small Outline Package (SOP), EIAJ TYPE II, 5.3mm Wide                |
| 74AC08MTC    | MTC14          | 14-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide  |
| 74AC08PC     | N14A           | 14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide       |
| 74ACT08SC    | M14A           | 14-Lead Small Outline Integrated Circuit (SOIC), JEDEC MS-012, 0.150" Narrow |
| 74ACT08MTC   | MTC14          | 14-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 4.4mm Wide  |
| 74ACT08PC    | N14A           | 14-Lead Plastic Dual-In-Line Package (PDIP), JEDEC MS-001, 0.300" Wide       |

Device also available in Tape and Reel. Specify by appending suffix letter "X" to the ordering number.




All packages are lead free per JEDEC: J-STD-020B standard.

### Connection Diagram



### Logic Symbol



### Pin Description

| Pin Names  | Description |
|------------|-------------|
| $A_n, B_n$ | Inputs      |
| $O_n$      | Outputs     |

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol                | Parameter                                    | Rating                   |
|-----------------------|----------------------------------------------|--------------------------|
| $V_{CC}$              | Supply Voltage                               | −0.5V to +7.0V           |
| $I_{IK}$              | DC Input Diode Current<br>$V_I = -0.5V$      | −20mA                    |
|                       | $V_I = V_{CC} + 0.5$                         | +20mA                    |
| $V_I$                 | DC Input Voltage                             | −0.5V to $V_{CC} + 0.5V$ |
| $I_{OK}$              | DC Output Diode Current<br>$V_O = -0.5V$     | −20mA                    |
|                       | $V_O = V_{CC} + 0.5V$                        | +20mA                    |
| $V_O$                 | DC Output Voltage                            | −0.5V to $V_{CC} + 0.5V$ |
| $I_O$                 | DC Output Source or Sink Current             | ±50mA                    |
| $I_{CC}$ or $I_{GND}$ | DC $V_{CC}$ or Ground Current per Output Pin | ±50mA                    |
| $T_{STG}$             | Storage Temperature                          | −65°C to +150°C          |
| $T_J$                 | Junction Temperature                         | 140°C                    |

## Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. ON Semiconductor does not recommend exceeding them or designing to absolute maximum ratings.

| Symbol                | Parameter                                                                                                  | Rating         |
|-----------------------|------------------------------------------------------------------------------------------------------------|----------------|
| $V_{CC}$              | Supply Voltage<br>AC                                                                                       | 2.0V to 6.0V   |
|                       | ACT                                                                                                        | 4.5V to 5.5V   |
| $V_I$                 | Input Voltage                                                                                              | 0V to $V_{CC}$ |
| $V_O$                 | Output Voltage                                                                                             | 0V to $V_{CC}$ |
| $T_A$                 | Operating Temperature                                                                                      | −40°C to +85°C |
| $\Delta V / \Delta t$ | Minimum Input Edge Rate, AC Devices:<br>$V_{IN}$ from 30% to 70% of $V_{CC}$ , $V_{CC}$ @ 3.3V, 4.5V, 5.5V | 125mV/ns       |
| $\Delta V / \Delta t$ | Minimum Input Edge Rate, ACT Devices:<br>$V_{IN}$ from 0.8V to 2.0V, $V_{CC}$ @ 4.5V, 5.5V                 | 125mV/ns       |

## DC Electrical Characteristics for AC

| Symbol                         | Parameter                                     | V <sub>CC</sub><br>(V) | Conditions                                                                                    | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> = −40°C to +85°C |  | Units |
|--------------------------------|-----------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------|------------------------|-------------------|---------------------------------|--|-------|
|                                |                                               |                        |                                                                                               | Typ.                   | Guaranteed Limits |                                 |  |       |
| V <sub>IH</sub>                | Minimum HIGH Level Input Voltage              | 3.0                    | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                             | 1.5                    | 2.1               | 2.1                             |  | V     |
|                                |                                               | 4.5                    |                                                                                               | 2.25                   | 3.15              | 3.15                            |  |       |
|                                |                                               | 5.5                    |                                                                                               | 2.75                   | 3.85              | 3.85                            |  |       |
| V <sub>IL</sub>                | Maximum LOW Level Input Voltage               | 3.0                    | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> − 0.1V                                             | 1.5                    | 0.9               | 0.9                             |  | V     |
|                                |                                               | 4.5                    |                                                                                               | 2.25                   | 1.35              | 1.35                            |  |       |
|                                |                                               | 5.5                    |                                                                                               | 2.75                   | 1.65              | 1.65                            |  |       |
| V <sub>OH</sub>                | Minimum HIGH Level Output Voltage             | 3.0                    | I <sub>OUT</sub> = −50μA                                                                      | 2.99                   | 2.9               | 2.9                             |  | V     |
|                                |                                               | 4.5                    |                                                                                               | 4.49                   | 4.4               | 4.4                             |  |       |
|                                |                                               | 5.5                    |                                                                                               | 5.49                   | 5.4               | 5.4                             |  |       |
|                                |                                               | 3.0                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = −12mA                |                        | 2.56              | 2.46                            |  |       |
|                                |                                               | 4.5                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = −24mA                |                        | 3.86              | 3.76                            |  |       |
|                                |                                               | 5.5                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = −24mA <sup>(1)</sup> |                        | 4.86              | 4.76                            |  |       |
| V <sub>OL</sub>                | Maximum LOW Level Output Voltage              | 3.0                    | I <sub>OUT</sub> = 50μA                                                                       | 0.002                  | 0.1               | 0.1                             |  | V     |
|                                |                                               | 4.5                    |                                                                                               | 0.001                  | 0.1               | 0.1                             |  |       |
|                                |                                               | 5.5                    |                                                                                               | 0.001                  | 0.1               | 0.1                             |  |       |
|                                |                                               | 3.0                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 12mA                 |                        | 0.36              | 0.44                            |  |       |
|                                |                                               | 4.5                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 24mA                 |                        | 0.36              | 0.44                            |  |       |
|                                |                                               | 5.5                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 24mA <sup>(1)</sup>  |                        | 0.36              | 0.44                            |  |       |
| I <sub>IN</sub> <sup>(3)</sup> | Maximum Input Leakage Current                 | 5.5                    | V <sub>I</sub> = V <sub>CC</sub> , GND                                                        |                        | ±0.1              | ±1.0                            |  | μA    |
| I <sub>OLD</sub>               | Minimum Dynamic Output Current <sup>(2)</sup> | 5.5                    | V <sub>OLD</sub> = 1.65V Max.                                                                 |                        |                   | 75                              |  | mA    |
| I <sub>OHD</sub>               |                                               | 5.5                    | V <sub>OHD</sub> = 3.85V Min.                                                                 |                        |                   | −75                             |  | mA    |
| I <sub>CC</sub> <sup>(3)</sup> | Maximum Quiescent Supply Current              | 5.5                    | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                      |                        | 2.0               | 20.0                            |  | μA    |

**Notes:**

1. All outputs loaded; thresholds on input associated with output under test.
2. Maximum test duration 2.0ms, one output loaded at a time.
3. I<sub>IN</sub> and I<sub>CC</sub> @ 3.0V are guaranteed to be less than or equal to the respective limit @ 5.5V V<sub>CC</sub>.

## DC Electrical Characteristics for ACT

| Symbol           | Parameter                                     | V <sub>CC</sub><br>(V) | Conditions                                                                                    | T <sub>A</sub> = +25°C |                   | T <sub>A</sub> = –40°C to +85°C |  | Units |
|------------------|-----------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------|------------------------|-------------------|---------------------------------|--|-------|
|                  |                                               |                        |                                                                                               | Typ.                   | Guaranteed Limits |                                 |  |       |
| V <sub>IH</sub>  | Minimum HIGH Level Input Voltage              | 4.5                    | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> – 0.1V                                             | 1.5                    | 2.0               | 2.0                             |  | V     |
|                  |                                               | 5.5                    |                                                                                               | 1.5                    | 2.0               | 2.0                             |  |       |
| V <sub>IL</sub>  | Maximum LOW Level Input Voltage               | 4.5                    | V <sub>OUT</sub> = 0.1V or V <sub>CC</sub> – 0.1V                                             | 1.5                    | 0.8               | 0.8                             |  | V     |
|                  |                                               | 5.5                    |                                                                                               | 1.5                    | 0.8               | 0.8                             |  |       |
| V <sub>OH</sub>  | Minimum HIGH Level Output Voltage             | 4.5                    | I <sub>OUT</sub> = –50μA                                                                      | 4.49                   | 4.4               | 4.4                             |  | V     |
|                  |                                               | 5.5                    |                                                                                               | 5.49                   | 5.4               | 5.4                             |  |       |
|                  |                                               | 4.5                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = –24mA                |                        | 3.86              | 3.76                            |  |       |
|                  |                                               | 5.5                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OH</sub> = –24mA <sup>(4)</sup> |                        | 4.86              | 4.76                            |  |       |
| V <sub>OL</sub>  | Maximum LOW Level Output Voltage              | 4.5                    | I <sub>OUT</sub> = 50μA                                                                       | 0.001                  | 0.1               | 0.1                             |  | V     |
|                  |                                               | 5.5                    |                                                                                               | 0.001                  | 0.1               | 0.1                             |  |       |
|                  |                                               | 4.5                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 24mA                 |                        | 0.36              | 0.44                            |  |       |
|                  |                                               | 5.5                    | V <sub>IN</sub> = V <sub>IL</sub> or V <sub>IH</sub> , I <sub>OL</sub> = 24mA <sup>(4)</sup>  |                        | 0.36              | 0.44                            |  |       |
| I <sub>IN</sub>  | Maximum Input Leakage Current                 | 5.5                    | V <sub>I</sub> = V <sub>CC</sub> , GND                                                        |                        | ±0.1              | ±1.0                            |  | μA    |
| I <sub>CCT</sub> | Maximum I <sub>CC</sub> /Input                | 5.5                    | V <sub>I</sub> = V <sub>CC</sub> – 2.1V                                                       | 0.6                    |                   | 1.5                             |  | mA    |
| I <sub>OLD</sub> | Minimum Dynamic Output Current <sup>(5)</sup> | 5.5                    | V <sub>OLD</sub> = 1.65V Max.                                                                 |                        |                   | 75                              |  | mA    |
| I <sub>OHD</sub> |                                               | 5.5                    | V <sub>OHD</sub> = 3.85V Min.                                                                 |                        |                   | –75                             |  | mA    |
| I <sub>CC</sub>  | Maximum Quiescent Supply Current              | 5.5                    | V <sub>IN</sub> = V <sub>CC</sub> or GND                                                      |                        | 4.0               | 40.0                            |  | μA    |

**Notes:**

4. All outputs loaded; thresholds on input associated with output under test.  
 5. Maximum test duration 2.0ms, one output loaded at a time.

**AC Electrical Characteristics for AC**

| Symbol    | Parameter         | $V_{CC}$ (V) <sup>(6)</sup> | $T_A = +25^\circ\text{C}$ ,<br>$C_L = 50\text{pF}$ |      |      | $T_A = -40^\circ\text{C to } +85^\circ\text{C}$ ,<br>$C_L = 50\text{pF}$ |      | Units |
|-----------|-------------------|-----------------------------|----------------------------------------------------|------|------|--------------------------------------------------------------------------|------|-------|
|           |                   |                             | Min.                                               | Typ. | Max. | Min.                                                                     | Max. |       |
| $t_{PLH}$ | Propagation Delay | 3.3                         | 1.5                                                | 7.5  | 9.5  | 1.0                                                                      | 10.0 | ns    |
|           |                   | 5.0                         | 1.5                                                | 5.5  | 7.5  | 1.0                                                                      | 8.5  |       |
| $t_{PHL}$ | Propagation Delay | 3.3                         | 1.5                                                | 7.0  | 8.5  | 1.0                                                                      | 9.0  | ns    |
|           |                   | 5.0                         | 1.5                                                | 5.5  | 7.0  | 1.0                                                                      | 7.5  |       |

**Note:**

6. Voltage range 3.3 is  $3.3\text{V} \pm 0.3\text{V}$ . Voltage range 5.0 is  $5.0\text{V} \pm 0.5\text{V}$ .

**AC Electrical Characteristics for ACT**

| Symbol    | Parameter         | $V_{CC}$ (V) <sup>(7)</sup> | $T_A = +25^\circ\text{C}$ ,<br>$C_L = 50\text{pF}$ |      |      | $T_A = -40^\circ\text{C to } +85^\circ\text{C}$ ,<br>$C_L = 50\text{pF}$ |      | Units |
|-----------|-------------------|-----------------------------|----------------------------------------------------|------|------|--------------------------------------------------------------------------|------|-------|
|           |                   |                             | Min.                                               | Typ. | Max. | Min.                                                                     | Max. |       |
| $t_{PLH}$ | Propagation Delay | 5.0                         | 1.0                                                | 6.5  | 9.0  | 1.0                                                                      | 10.0 | ns    |
| $t_{PHL}$ | Propagation Delay | 5.0                         | 1.0                                                | 6.5  | 9.0  | 1.0                                                                      | 10.0 | ns    |

**Note:**

7. Voltage range 5.0 is  $5.0\text{V} \pm 0.5\text{V}$ .

**Capacitance**

| Symbol   | Parameter                     | Conditions             | Typ. | Units |
|----------|-------------------------------|------------------------|------|-------|
| $C_{IN}$ | Input Capacitance             | $V_{CC} = \text{OPEN}$ | 4.5  | pF    |
| $C_{PD}$ | Power Dissipation Capacitance | $V_{CC} = 5.0\text{V}$ | 20.0 | pF    |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5817-1050

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative