

isc Silicon NPN Power Transistor

BUF405AXI

DESCRIPTION

- High Voltage
- High Speed Switching

APPLICATIONS



- Designed for high reliability industrial and professional power driving applications such as motor drivers and off-line switching power supplies.

ABSOLUTE MAXIMUM RATINGS (Ta=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
VCEV	Collector-Emitter Voltage VBE= -1.5V	1000	V
VCEO	Collector-Emitter Voltage	450	V
VEBO	Emitter-Base Voltage	7	V
IC	Collector Current-Continuous	7.5	A
ICM	Collector Current-Peak	15	A
IB	Base Current-Continuous	3	A
IBM	Base Current-peak	4.5	A
PC	Collector Power Dissipation @TC=25℃	39	W
Tj	Junction Temperature	150	℃
Tstg	Storage Temperature Range	-65~150	℃

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
Rth j-c	Thermal Resistance,Junction to Case	3.2	℃/W



isc Silicon NPN Power Transistor

BUF405AXI

ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEQ(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=0.2\text{A}$; $I_B=0$; $L=25\text{mH}$	450			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage	$I_E=50\text{mA}$; $I_C=0$	7			V
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C=2.5\text{A}$; $I_B=0.25\text{A}$		0.8		V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C=5\text{A}$; $I_B=1\text{A}$		0.5		V
$V_{BE(sat)-1}$	Base-Emitter Saturation Voltage	$I_C=2.5\text{A}$; $I_B=0.25\text{A}$		0.9		V
$V_{BE(sat)-2}$	Base-Emitter Saturation Voltage	$I_C=5\text{A}$; $I_B=1\text{A}$		1.1		V
I_{CER}	Collector Cutoff Current	$V_{CE}=V_{CEV}$; $R_{BE}=5\Omega$ $V_{CE}=V_{CEV}$; $R_{BE}=5\Omega$; $T_C=100^{\circ}\text{C}$			0.1 0.5	mA
I_{CEV}	Collector Cutoff Current	$V_{CE}=V_{CEV}$; $V_{BE}=-1.5\text{V}$ $V_{CE}=V_{CEV}$; $V_{BE}=-1.5\text{V}$; $T_C=100^{\circ}\text{C}$			0.1 0.5	mA
I_{EBO}	Emitter Cutoff Current	$V_{EB}=5\text{V}$; $I_C=0$			1.0	mA

Switching Times

t_s	Storage Time	$I_C=2.5\text{A}$; $I_{B1}=0.25\text{A}$; $V_{CC}=50\text{V}$; $V_{BB}=-5\text{V}$; $R_{BB}=2.4\Omega$; $L=1\text{mH}$ $V_{clamp}=400\text{V}$		0.8		μS
t_f	Fall Time			0.05		μS